

BS1154-Y50 Natural Rubber



DRN52 DATA SHEET

DELTA RUBBER LIMITED

Unit 21 Priory Industrial Park, Airspeed Road
Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

Description

DRN52 White BS 1154 Y40 specification high-quality Natural 50° shore A material, suitable for a wide range of applications with excellent resilience, tear & abrasion resistance & high tensile strength. Resistant to water, mild chemicals etc. High Electrical resistance.

Technical Information

Material:	NR Natural Rubber to BS Specification Grade
Application:	General Purpose, Water Resistant, Mechanical
Thickness:	0.5,1,1.5,2,3,5,6mm
Colour:	White
Cloth/Plate Finish:	Plate
Density [specific gravity]:	1.10
Hardness [Degrees Shore A]:	50° ± 5°
Tensile Strength [MPA]:	18 min
Elongation at Break:	500%
Minimum Temperature:	-20°C
Maximum Temperature:	+70°C
Compression Set:	30%
Abrasion Resistance:	125

Thickness

0.5mm-6mm
(other thicknesses on request)

Sheet Size

1.4m wide x 5,10m rolls

Finish

Plate

Cutting

Standard Press Tools

