# Beige FDA Fluoro-A Rubber Sheet



## DFKM Beige

**DATA SHEET** 

#### DELTA RUBBER LIMITED

Unit 21 Priory Industrial Park, Airspeed Road Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

### Description

Viton FKM sheet in standard beige food industry colour, making contamination identification easier.

#### **Technical Information**

Colour: Beige

FKM Type: 'A' Type Di-Polymer- 66% Fluorine Content

Hardness: 64° Shore A ± 5°

Specific Gravity: 2.02g cm3

Tensile Strength: 14 Mpa Flongation at Break: 250%

Elongation at Break: 250% Compresssion Set: 18%

Working Temperature: -10°C to +250°C

#### **Thickness**

1.5mm-3mm (other thicknesses on request)

**Sheet Size** 

1.2m x 5/10m Rolls

Finish

Plate Finish

#### **Further Information**

All ingredients used in this product are listed on the FDA whitelist as described in the FDA code of Federal Regulations Title 21. Section 177. 2600. This has been independently tested by SGS international and are ceritfied as meeting the migration values set out in FDA regulations Title 21. Section 177. 2600 'Rubber Artiles Inteneded for Repeated Use.





