

Statite Oil Proof Gasket Paper



STAT DATA SHEET

DELTA RUBBER LIMITED

Unit 21 Priory Industrial Park, Airspeed Road
Christchurch, Dorset, BH23 4HD

t: 01425 278011 www.deltarubber.co.uk deltasales@deltarubber.co.uk

Description

This impregnated paper gasket material provides reliable sealing at a relatively low cost. Impregnated paper is very suited to gasket manufacturing. Extensively used in the automotive industry for low pressure applications with oils and fuels.

Technical Information

Colour:	Buff both sides
Compressibility (ATSM F36J):	12-16%
Recovery (ATSM F36J):	25-45%
Maximum Continuous Service Temperature:	120 C
Maximum Pressure:	8bar
Minimum Tensile Strength (ASTM F152):	>13 N/mm ²
Thickness increase after immersion in:	
Oil IRM 903 5h/150 C	<5%
Fuel B 5h/23 C	<5%
Water 5h/23 C	<30%
Weight increase after immersion in:	
Oil IRM 903 5h/150 C	<15%
Fuel B 5h/23 C	<15%
Water 5h/23 C	<90%
Density	0.7g g/cm ³

Thickness

0.25mm – 0.80mm

Sheet Size

1m x 5,10m Rolls

Colour

Buff both sides

Cutting

Standard Press Tools

(Based on 0.8mm thick sample)

